

Technical Information

Model: Onyx

- Double Flat Panel Radiator.
- Best Value for the money.
- A++ Energy saving Grade. "More Heat- Less cost"
- Made from 99.97% Pure Aluminum.
- High Surface area due to "Micro Fin Technology"
- "Low Temperature Technology" Heat up quickly and efficiently even at low water flow and low water temperature.
- Compatible with thermostatic valves, central heating, heat pumps and solar panel heat supplies.
- No- Corrosion Technology.
- Resistance to excess pressure up to 50 Bars.
- Light weight and easy to install.
- Equipped with height adjustable brackets.
- Tested and Certified to BS EN 442 Standards.
- CE Marked
- 10 Years Guarantee.
- Pipe Centers are the width of the radiator plus the valves.
- Distance from Wall to Centre: 60 mm.

Stocked Finishes and Sizes:

White / Black

Height (mm)	Width (mm)	Pipe Centre (mm)	Number of Columns	Heat Output Delta T: 50°C
				(Btu/hr.)
400	1000	1070	14	4286
	1200	1270	17	5205
	1330	1400	19	5817
500	500	570	7	2682
	800	870	11	5705
	1000	1070	14	5357
	1200	1270	17	6506
	1330	1400	19	7271
600	500	570	7	3219
	800	870	11	5059
	1000	1070	14	6440
	1200	1270	17	7819
	1330	1400	19	8739